

Installation Instructions for UL924 Listed Photoluminescent Exit Sign

CAUTION: EXTERNAL ILLUMINATION SOURCE REQUIRED

Install only in a location where a minimum of 5 foot candles (54 lux) of fluorescent lighting is available on the sign face at all times of building occupancy.

INSTALLATION:

- ♦ The sign must be charged for a minimum of 60 minutes to become fully operational.
- ♦ The external illumination source must be reliable and supplied by a circuit not controlled by automatic timers or sensors, and whose controls are accessible only to authorized personnel.
- ♦ The external illumination source is to be energized at all times during building occupancy.
- ♦ Lighting levels on the sign face are to be reassessed after any changes in external lighting types or levels to determine that the sign is still being illuminated in accordance with its listing.
- ♦ Cleaning of the sign face should be done with a non-abrasive cloth dampened with water. Do not use chemical solvents of any kind.
- ♦ Periodic visibility inspections are to be performed regularly and in accordance with the applicable installation code (such as NFPA 101).
- ♦ Install this sign indoors only, where not exposed to direct sunlight, liquid spray or temperatures outside of the range +10 to +40° C (50 -104° F).

CHEVRONS:

Sign models that use detachable chevrons include 2 peel and stick directional chevrons that may be applied to the area of the sign face designated by dots to indicate exit direction. Do not apply both chevrons to indicate the same direction.

DIMENSIONS:

Available in 2 sizes: (a) No Chevrons 8.5"x11" or (b) With Detachable Chevrons 8.5"x14.75".

VIEWING DISTANCE:

UL924 listed 50-foot (15.25 meters) Maximum Legible Viewing Distance (*File E325381*)



MOUNTING:

Mounting holes are provided for unframed signs. Mark the mounting hole location on the wall. Drill the holes and screw the exit sign to the wall through the mounting holes.

WARRANTY:

20 year limited warranty against manufacturer defects and workmanship. Made in USA.

EXIT SIGN MODELS:

GE50 - Green Background (No Chevrons)

GE50D - Green Background (Detachable Chevrons)

RE50 - Red Background (No Chevrons)

RE50D - Red Background (Detachable Chevrons)

BE50 - Black Background (No Chevrons)

BE50D - Black Background (Detachable Chevrons)

SAVE THESE INSTRUCTIONS