



## CONSTRUCTION

The COMBOJR2-R series is constructed from injection molded, impact- and scratch-resistant and corrosion-proof UL 94 V-0 flame retardant thermoplastic housing. White housing is standard.

## ILLUMINATION

Uses two 1.5W LED lamp heads each equipped with 12 seriesparallel white LEDs. Lamp heads are on track-and-swivel guides. Glare-free lenses provide redundant light source to ensure performance in emergency situations. EXIT portion uses long-lasting, efficient red or green LEDs.

## ELECTRICAL COMPONENTS

Dual voltage input 120/277 VAC operation. LED display indicates AC/ON. An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit. Unit offers surge protected, solid state circuitry.

## EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 90 minutes. The fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## BATTERY - BATTERY BACKUP


The COMBOJR2-R Combo Exit Light series is designed with a maintenance-free 3.6V 900mAh NiCad battery (Battery Backup & Self Testing Models) or a 3.6V 1800 mAh battery (Remote Head Capable Models) that provides a minimum emergency duration of 90 minutes. Recharge time of the battery is 24 hours.

## PHOTOMETRICS

Standard mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 24ft for a 3ft path of egress.

Standard mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 18ft for a 6ft path of egress.

Compact Red LED Exit Light Combo | High Output | Adjustable Heads Photometrics



## SELF-TESTING OPTION

Unit continuously monitors the AC power, battery supply voltage, emergency lamp condition and charging circuit. If failure is detected, the indicator will show status and correct when adjusted. Unit will automatically perform NFPA required monthly and annual testing. Refer to user manual for details.

## OPERATIONAL TEMPERATURE

### Temperature Ratings

Standard Option	20°C to 30°C / 68°F to 86°F
-----------------	-----------------------------


## REMOTE HEAD CAPABLE OPTION

The remote head capability option allows the COMBOJR2-R unit to supply power to up to two additional LED remote heads. The remote heads would then operate on the same emergency mode as the standard units (see Emergency Operation Section).

## INSTALLATION

The COMBOJR2-R is suitable for surface wall and top mounting via included canopy. Unibody housing snaps together with no additional fasteners. Quick connect installation design allows for quick and easy installation. Knock-out chevrons for customized egress signage and field adjustable.

## DIMENSIONS



Weight : 10.00 lb