

Application Instruction

IMPORTANT: Minimize touching adhesive with fingers

Flexible Signs

- 1) With clean, dry hands peel protective liner back about 2” from one end and position piece on surface. Continue to remove liner. Press product firmly in place as liner is removed.
- 2) For small pieces: Peel liner off piece. Holding piece by its edges, curve it gently with the adhesive side out. Align the middle of the piece with the middle of the target surface and press down.
- 3) Finally, press piece into firm contact with surface starting in the middle and working out towards the edges.

Rigid Signs

- **Foam Tape**

- 1) With clean, dry hands remove piece from pad and apply to surface or product.
- 2) Remove release liner from applied die cut piece.
- 3) Align product and press into firm contact with surface starting in the middle and working out towards the edges.

- **Mechanically Fasten**

- 1) Make a line on the wall to mark where the top and side of the sign will be located.
- 2) Hold the sign to the lines and mark the studs or spots you will be drilling the holes for your mounting hardware. Be sure to mark both the wall and sign so they are in alignment. Then, drill your holes. If you are using wall anchors tap them in at this time.
- 3) Secure the sign to the wall.

There may be additional application methods for the Glo Brite® signs, however it is the sole responsibility of the user / installer to test compatibility and determine its suitability for the intended application.

Product Certification

All NYC Department of Buildings, Materials and Equipment Acceptance Division, approved Glo Brite® products provided are equivalent to those tested and accepted for use, as provided in Section 27-131 of the New York City Building Code.

Important Procedures for Proper Application and Service Life

- All surfaces must be smooth, clean, dry, oil free and at minimum recommended surface temperature (50°F) before applying product.
- Testing of adhesion to the surface must be done prior to installation.
- Remove any loose residue from surface.
- Rough or porous surfaces must be primed.
- Remove chipped, cracked or peeled paint and repair or replace any broken or damaged surface prior to application.
- Seal porous surfaces, fill in cracks and repair to a smooth finish.
- Treated or untreated wood must be painted prior to application of pressure sensitive tape products.
- Rubber hand rollers should be used to assure a firm bond when applying all pressure sensitive tape materials.
- Pressure sensitive tapes can be applied on most painted surfaces that are in good condition. The tape materials will only adhere to the underlying surface as well as the paint base. Painted surfaces must be thoroughly dry before application of pressure sensitive tape materials.
- DO NOT apply pressure sensitive tape materials on surfaces with constant water contact or moisture seepage.
- DO NOT apply pressure sensitive tape materials over grouting. Also, avoid cracks in concrete and breaks in all surfaces.
- DO NOT use Glo Brite® products in dark or dimly lit areas. Photoluminescent materials require exposure to light in order to perform properly. Test light levels and ensure product face is exposed to the minimum required amount at all times.
- Store product in its original carton preferably at 72°F and 50% relative humidity.
- It is recommended to use product within 1 year of shipment from manufacturer.

Maintenance Instructions

To maintain product effectiveness, the application must be inspected regularly. The Glo Brite® materials should be kept free of dirt and other residue that might impair functionality. Product should be inspected on a monthly basis and cleaned per procedures as needed.

- Glo Brite® Flexible and Rigid Signs:
 - 1) Under normal conditions, simply wiping the Glo Brite® material with a damp cloth will remove any dust or residue.
 - 2) Heavily soiled areas may require the use of general purpose household cleaner / degreaser* and a soft cloth, followed by a wipe with a damp cloth.
 - 3) If soils cannot be removed, the Glo Brite® product must be replaced.

* Such as Formula 409®. Follow manufacturer's instructions for use and safety precautions. Test cleaner on a small area of the Glo Brite® to ensure compatibility of products.