



FEATURES

- For 120V
- 2.8 watts per kit
- Brightest conversion kit
- Bayonet, intermediate, or candelabra base socket adapters supplied

WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

Conformance to Codes and Standards

The RETROG kit meets or exceeds the following codes: UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Code.



ORDERING INFORMATION

Series	Base Adapters	Voltage
RETROG	STD (Standard Size Adapters)	120 (120V)
	MD (Medium Size Adapters)	120-DF (120V + Green Diffuser)

ILLUMINATION

With the RETROG kit easily convert incandescent exit signs to energy efficient LED Exit signs. Ultra bright, long-life green LED.

ELECTRICAL COMPONENTS

The RETROG kit is designed for 120V application only. Energy usage of 2.8W per kit

INSTALLATION

The RETROG Kits are supplied with socket adapters for installation in signs with bayonet, intermediate, or candelabra bases.

DIMENSIONS

