

FEATURES

- Full Range of Amperage capacities
- Valve regulated, spill proof construction, ABS container
- Operating Temperature range of 50°F (10°C) to 75°F (24°C)

WARRANTY

A battery determined to be defective within the warranty period shall be repaired or replaced at a cost equal to the net price in effect at the time, reduced by the percentage in effect by prorating. Warranty is void if batteries are not maintained and/or installed according to specifications. Liability extends to the repair/replacements of the battery only, buyer is responsible for all costs to de-install defective products and re-install defective product and re-install replacement repaired products. For full warranty details, visit our Warranty Section.



Battery Information						
Series	B6V1-2AH	B6V23A	B6V4A	B6V7A	B6V10A	B6V12A
Height	2"	2.99"	3.94"	3.70"	3.70"	3.70"
Height (Includes Leads)	2.2"	2.99"	4.25"	3.94"	3.86"	3.86"
Length	3.82"	1.46"	2.76"	5.95"	5.95"	5.95"
Width	.94"	1.69"	1.86"	1.34"	2"	2"
Weight	.66 Lbs.	5h	1.60 Lbs.	2.42 Lbs.	4.30 Lbs.	4.30 Lbs.
Max Discharge Current (5 Sec)	40 A	28 A	45 A	70 A	110 A	120 A
Standard Terminals	FO-O1	FO-O2	FO-O2	FO-O2/03	FO-O2/03	FO-O2/03
-20Hrs	@0.06A, 1.2Ah	@0.14A, 2.8Ah	@.225A, 4.5Ah	@0.35A, 7.0Ah	@0.5A, 10Ah	@0.6A, 12Ah
-5Hrs	@0.192A, 0.96Ah	@0.45A, 2.25Ah	@.072A, 2.7Ah	@1.12A, 5.6Ah	@1.7A, 8Ah	@1.92A, 9.6Ah
-1Hr	@0.72A, .72Ah	@1.68A, 1.68Ah	@2.7A, 2.7Ah	@4.2A, 4.2Ah	@6.2A, 6.2Ah	@7.2A, 7.2Ah
Internal Resistance	50M	35M	20M	15M	11M	8M
Charging Voltage - Standby	2.2750.025 V/CELL	2.2750.025 V/CELL	2.2750.025 V/CELL	2.2750.025 V/CELL	2.2750.025 V/CELL	2.2750.025 V/CELL
Charging Voltage - Cycle	2.450.05 v/ CELL					
Max Charge Current	0.36 A	0.84 A	1.35 A	2.1 A	3.0 A	3.6 A